



THE HONG KONG
POLYTECHNIC UNIVERSITY
香港理工大學



香港太陽能學會
Solar Energy Society of Hong Kong

可再生能源建筑应用技术与展望

Prof. YANG Hongxing
杨洪兴

香港理工大学屋宇设备工程学系可再生能源研究室 教授

香港太阳能学会 会长



内容

- ✓ 可再生能源建筑应用技术简介
- ✓ 太阳能建筑光热和光电技术应用现状
- ✓ 太阳能光伏建筑一体化技术的发展与展望
- ✓ 光伏建筑一体化技术的研究
- ✓ 地源热泵技术在冬暖下热地区的应用研究
- ✓ 太阳能干燥除湿空调技术的研究
- ✓ 结论



可再生能源建筑应用技术简介

- 建筑耗能：中国大陆达47%^[1]，香港特区达60%^[2]
- 建筑上可再生能源利用技术：
 - 被动式太阳房技术
 - 太阳能热水生产技术
 - 太阳能光伏技术
 - 太阳能辅助制冷，除湿空调技术
 - 风能利用技术
 - 地源热泵技术
 - 废物利用技术，如固体垃圾和污水处理能源再利用等技术

[1] T. Huo et al. (2019), *Science of the Total Environment*. Volume 650, Pages 427-437. [2] X. Chen, H. Yang (2017). *Applied Energy*. Volume 206, Pages 541-557.






研究方向：发展以零能耗建筑为目标的电网-建筑-系统能源技术与管理机制

可再生能源-蓄能混合系统对建筑能耗和电网的影响机理和能源管理系统（EMS）设计



屋顶光伏 立面
光伏 微型垂直
轴风机 集热器
被动式太阳房



1.建筑

需求侧:

建筑围护结构
空调系统 生
活热水
照明




蓄能:

电池、飞轮等

电网:

电价
稳定性
灵活性



模型预测控制（MPC）

1. BIPV applications

-Building integrated Photovoltaics (BIPV)

BIPV: refers to using photovoltaic materials, viz. solar cells and PV modules, to replace conventional building materials in parts of the building envelope such as the roof, skylights, windows or facades where the PV modules simultaneously serving as building envelope material and generating power.



Future trend of solar photovoltaic applications

——Building integrated Photovoltaics (BIPV)

Functions of BIPV

- Power generator
- Part of construction materials
- Water proof
- Shading
- Noise barrier
- Insulation
- Natural lighting






Figure 1. Multiple functions of PV modules. Source: Multielement project

BIPV applications



An overview of applications of PV modules in buildings.

BIPV projects-rooftop




BIPV facade



BIPV Projects

□ Skylight and atrium



□ Shading type



BIPV of the South Railway Station in Nanjing



Installation capacity: 10.67 MW.

(The biggest single BIPV project in the world)

PV module type: Poly-Si

Annual energy output: 9.12 GWh

Annual CO₂ emission reduction: 9000 tons



BIPV of the Museum of Natural Science in Jiangxi



Installation
capacity: 3.05 MW
PV module type: a-Si hollow PV
module
Installation method:
BIPV on facades
and roof

BIPV of Zhujiang City in Guangzhou



Installation
capacity: 185 kW
PV module type: a-
Si PV module
Installation method:
BIPV on the east
and west facades

BIPV in Huangshi of Hubei



Installation capacity:

3 MW

PV module type:

Poly-Si PV module

Installation method:

BIPV on facades,
roofs and shading
panels

BIPV of Hanergy in Jiangsu



Installation capacity:
67 KW

PV module type: a-Si PV module

Installation method:
BIPV on facades

Annual energy
output: 33919 kWh

Annual CO₂
emission reduction:
10 tons

New BIPV claddings from Hanergy

COMMERCIAL APPLICATION
• THIN-FILM SOLAR
SOLUTION



The household solar project in Guoyuan Community of Xucheng Town in Xuyi County of Jiangsu (Installed capacity: 4 kWp)




The household solar project on No. 2 Huaxia Road of Pudong New Area in Shanghai (Installed capacity: 1.5 kWp)



The household solar project in Huadu District of Guangzhou (Installed capacity: 33 kWp)



The household solar project of Shoufu Villa in Hualbei of Anhui (Installed capacity: 264 kWp)



BIPV applications in Taiwan



1MWp at Kaohsiung National Stadium
(2009)

Table 1: Annual radiation comparison across different latitude [12, 13].

	Latitude	Annual solar radiation (Wh/m ² /year)
Taiwan-1 (Max)		1,560
Taiwan-2 (Average)	±23°N	1,059
Taiwan-3 (Min)		801
Sahara	25°00'N	2,500
Israel	33°00'N	2,000
Los Angeles, USA	34°30'N	1,816
Athens, G	37°58'N	1,580
Trapani, I	38°00'N	1,800
New York, USA	40°47'N	1,424
Rome, I	41°48'N	1,529
Toronto, C	43°40'N	1,380
Freiburg, D	48°00'N	1,100
London, UK	51°29'N	898
Berlin, G	52°28'N	1,026
Helsinki, FIN	60°00'N	950
Lerwick, UK	60°00'N	775



Solar PV utilizations in Hong Kong



PolyU in 1999

Wai Chai Tower



Lamma Power Plant



EMSD HQ in Hong Kong

Siu Ho Wan Sewage Treatment Plant

- Largest Solar Farm in Hong Kong
- Commissioned in 2016
- Located in North Lantau Island
- Polycrystalline PV panels



Solar Farm Area C



Solar Farm Area A & B

Floating PV in Hong Kong

Two Pilot Projects in Hong Kong

- Shek Pik Reservoir
- Plover Cove Reservoir



Location of FPV System	Annual Power generation (kWh)	Annual Carbon Dioxide Reduction (kg)
Shek Pik Reservoir	94,109	66,606
Plover Cove Reservoir	72,227	50,558



Details of the FiT in Hong Kong

Three types of FiT rates will be offered according to the installation capacity of your RE system:

Capacity of the Renewable Energy System	FiT rate (per unit of electricity -kWh)
≤ 10 kW	HK\$ 5
> 10 kW - ≤ 200 kW	HK\$ 4
> 200 kW - ≤ 1 MW	HK\$ 3

The rates listed above are effective from 1 Oct 2018 onwards and will be reviewed regularly.



A sample local village house rooftop PV system



Comparisons of a solar PV on a residential house

PV installation capacity: 3.0 kWp

Average net tariff in 2018

HK\$1.154 per kWh

Electricity generation by a small solar PV system without FiT

Installation cost

HK\$7900

Annual electricity generation

3,300 kWh

Annual earnings

HK\$3808.2

Payback Period

21 years

Electricity generation by a small solar PV system with FiT

Installation cost

HK\$54000

Annual electricity generation

3,300 kWh

FiT tariff

HK\$5.0

Annual earnings

HK\$16,500

Payback Period

3.3 years




BIPV potential study in Europe

Available Roof Surface					
	Net Available Solar Surface (Km ²)	Installable PV "Potential" (GW)	Estimated Electricity production (Twh/year)	Residential Electricity consumption 2006 (TWh/year)	% of PV
Europe (75%: Germany, France, UK, Italy, Spain)	3.723	465,4 (8m ² /Kwp)	511,9	859	59%
		161,9 (23m ² /KWp)	178,1		20%
USA	4.563	570,4 (8m ² /Kwp)	570,4	1351	42%
		198,4(23m ² /KWp)	198,4		14%
Japan	1.050	131,3 (8m ² /Kwp)	118,1	229	51%
		45,7 (23m ² /KWp)	41,1		18%

** Facades not included*




The global BIPV sales will triple by 2019,
growth by 18.7%;
Currently the BIPV market holds a market
share of around 2% of the overall PV
market, 13% by 2022.





BIPV market

Current and forecasted BIPV market in € Millions



The most evolved BIPV market regions are Europe and the USA which combined currently account for around 70% of the worldwide market share.

Source: Nanomarkets , "Nanomarkets report BIPV Market Analysis and Forecast 2014-2021," 2015



2. Our research activities in BIPV applications:

(1) Potential BIPN in Hong Kong



- The potential total active rooftop area of PV modules was calculated as **37.4km²**. The total potential installation capacity is estimated as **5.97 GWp**. $A_{act.} = \frac{A_{pot.}}{A_{occu.}} \times A_{pv}$

$$E_{potential} = A_{act.} \times G_{optimal} \times \eta_{stc} \times \lambda$$

- The potential PV electricity output is about **5,981GWh**, accounting for **14.2%** of the total electricity use in 2011.
- Reduce the imports of coal and natural gas by 25% and 54% respectively and mitigate about **3 million tons** of GHG emissions yearly.



BIPV windows






Study of the overall energy performance of BIPV facade:

- real-time power generation performance
- thermal performance
- natural lighting performance





Annual overall performance in Hong Kong



- The maximum monthly energy output : 5.6 kWh/m²
- Annual energy output: 38 kWh/m²
- Saving cooling energy use: 70 kWh/m²/yr.
- Lighting can be powered by the PV-DSF itself in winter.



Experimental studies



PV-IGU



PV-DSF



PV shading

BIPV test bed at Tung Chung



The Housing Authority BIPV project

- Roof integration
- PV walls
- PV windows





Study on semi-transparent solar PV windows

- Data acquisition system





Study on semi-transparent solar PV windows

- Inside views of PV windows



Ventilated PV window

Efficiency: 6.8%


Transmittance: 20%

Rated power: 68W/m²

Efficiency: 6.3%

Transmittance: 20%


Rated power: 63W/m²




Hollow PV window



Energy performance of PV DSF and PV IGU



PV double skin façade




PV insulating glass unit

The heat transfer model, daylighting model and PV power generation model in EnergyPlus were adopted to investigate the corresponding performance simultaneously.




Structures of PV-IGU and PV-DSF

PV-IGU




PV-DSF






Experimental studies


Power output of PV-IGU on a typical sunny day




Power output of PV-DSF on a typical sunny day



Power output of solar PV shading on a typical sunny day





Monthly power output of PV systems





(3) Single-glazed PV glazing VS energy-efficient glazing


A generic representative model



Continuous dimming control

Simulation tools:

Berkeley Lab WINDOW, EnergyPlus




Sandia Array performance Model

- Empirical-based
- More accurate for thin-film solar cells




Single-glazed PV glazing

Power generation performance in Hong Kong



Monthly power output per unit area of south facing solar PV windows




Annual power outputs per unit area of solar PV windows in different orientations

- 1) Significant difference among different months: **more in winter and less in summer.**
- 2) Annual electricity output varies with orientations: **SW** > **SSW** > **WSW** > **S** > ... > **E**



Energy performance of PV-IGU

Annual PV power output



Location: Beijing > Harbin > Kunming > Shanghai > Hong Kong
Higher transmittance → Lower power output




Energy performance of PV-DSF


Model development and validation




Test bed




Simulation model



Window heat gain



Daylighting illuminance




Power output



Energy performance of PV-DSF

Energy saving potential of PV-DSF and PV-IGU compared to reference window



How to improve?


- Inner glazing
- Ventilation mode




Energy saving potential of solar PV shadings

Research gap

- Daylighting performance is rarely considered in previous studies. However, both external and internal shadings affect the daylighting performance of the room.
- Comparison between external solar PV shadings and interior shading devices has not been reported yet.



Simulation model of solar PV shadings




Validation of the electricity output

Due south, Tilt angle: 55°, Error: 5%




(3) *Advanced VPV IGU*

- A novel vacuum PV insulated glass unit (VPV IGU) is proposed to combine the advantage of the high thermal insulation performance of vacuum glazing and the power generation capability of STPV windows.



The structural details of VPV IGU




The cross-section of VPV IGU



Power generation Performance

- The difference of the power generation among different BIPV systems is less than 1%, and the single-pane PV glazing produced the most electricity output.





(4) Development of self-cleaning nano-coating for PV



Super-hydrophobic , θ (Lotus leaf): $>150^\circ$

Super-hydrophobic self-cleaning glass



Super-hydrophilic , θ (clean glass surface) : $<10^\circ$

Super-hydrophilic self-cleaning glass



Advantages of our product: Superior self-cleaning property and cheaper cost



The comparison between two PV modules after two months in Shenzhen.
The self-cleaning coating has superior super-hydrophilicity.



Advantages of our product: Superior self-cleaning property and cheaper cost

With self-cleaning coating



Without self-cleaning coating




Comparisons between two PV modules after about one year in Hong Kong.
The self-cleaning coating has superior super-hydrophilicity.



(4) Selection of PV modules

Global Annual PV Shipments by Technology*



In 2017:

- Monocrystalline: 45%;
- Poly-crystalline: 51%;
- Thin film: 4%。



Experimental study



The PV system testing rig in the New Territories

In order to obtain the actual energy performance of PV modules, an on-site test system was developed in Hong Kong. All the ten solar PV panels are installed facing south with a tilt angle of 22° .




Selection of solar PV panels for detailed study -- 5 different types

Solar Cell-technologies	Mono-Si 1	Mono-Si 2	Poly-Si 1	Poly-Si 2	A-Si 1	A-Si 2	CIGS 1	CIGS 2	CdTe 1	CdTe 2
Model										
Nominal Power (W)	305	300	280	275	140	130	140	115	107.5	80
Short circuit current (A)	9.94	9.77	9.37	9.35	5.28	2.65	1.79	4.52	1.75	0.95
Open circuit voltage (V)	40.2	39.76	38.65	38.72	42.3	71	106.7	37.6	86.6	118.9
Current at maximum power (A)	9.24	9.26	8.86	8.77	4.34	2.22	1.62	3.87	1.57	0.85
Voltage at maximum power (V)	33.0	32.41	31.61	31.36	32.2	54	86.5	29.7	68.6	94.1
Maximum system voltage (V)	1000 (IEC)	1000 (IEC) 1000 (UL)	1000/1500 DC(IEC)	1000 (IEC) 1000 (UL)	N/A	1000	1000 (IEC) 600 CSA/UL	1000 (IEC) 600 (UL)	1000V (class II) 1500V class 0	N/A
Module Efficiency (%)	18.7	18.0	17.1	16.5	9.6	9.1	14.9	12.0	14.9	11.1
Weight (kg)	18.2	18.8	18.2	18.8	18.3	25	16.5	2.7	12	11.8
Dimension (mm × mm × mm)	1650*991*40	1670*1000*32	1650*991*35	1670*1000*32	1310*1110*40	1300*1100*6.8	1190*790*7.3	2598*370*17	1200*600*6.8	1200*600*6.8



Daily power generation from the whole system




The PV system has been working very well for 10 months. The highest daily energy output is 10.6 kWh on 30th November 2018.



Hourly average efficiency of PV modules

In typical sunny days (30th Oct and 6th Nov 2018):




Energy conversion efficiencies:

Mono-Si > CdTe (107.5Wp) > Poly-Si > CIGS > A-Si



Hourly average efficiency of PV modules

In typical
cloudy days
(2nd Nov and
3rd Nov 2018):








Energy conversion efficiencies:

Mono-Si > CdTe (107.5Wp) > Poly-Si >> CIGS > A-Si



Simulation of annual power generation for different tilt angles (south)



The optimal tilt angles of PV modules are found to be 18-22° depending on local latitude and weather.




Simulation results: Annual power generation at best position (azimuth=180°, and tilt angle=22°)

Solar PV panel	Mono-Si 305W	Mono-Si 300W	Poly-Si 280W	Poly-Si 275W	A-Si 140W	A-Si 130W	CIGS 140W	Flexible CIGS 115W	CdTe 80W	CdTe 107.5 W
Annual total (kWh)	354.1	334.4	316.7	310.6	142.6	136.8	146.6	129.4	81.3	143.2
Annual output (kWh/m ²)	215.9	200.2	193.1	186.0	98.3	95.7	156.0	134.8	112.9	198.9
Annual output (kWh/Wp)	1.16	1.11	1.13	1.13	1.02	1.05	1.05	1.12	1.02	1.33

Per m² (kWh/m²): Mono-Si > CdTe > Poly-Si > CIGS > a-Si

Energy yield (kWh/Wp): CdTe (107.5Wp) > Mono-Si > Poly-Si > CIGS > A-Si

3. Solar liquid desiccant air-conditioning (SLDAC)




Equipment



- Dehumidifier
- Solar Collector/ Regenerator
- Solution storage tank
- Heat exchanger
- Green line: Air flow path
 - Supplied by outdoor air fan
 - Moisture is removed in dehumidifier
 - Further cooled by AHU

Possible Configurations of the System

Liquid Desiccant System



Annual energy performance – bigger share in latent load



Solar Desiccant Air Conditioning


-----solar assisted air conditioning

Moisture Control → Desiccant Dehumidification → Latent Load

Temperature Control → Air cooling → Sensible Load

Separate handling of latent and sensible loads.

The Desiccant Dehumidifier



Raschig Ring




Berl Saddlen




Pall Ring


The Open Cycle Solar Collector/Regenerator




Possible Configurations of the System



Parametric analysis




(a) Solar radiation




(b) Solution temperature

Effects of the main parameters on a solar C/R

System Performance on Design Day



Energy savings for low latent load condition (SHF=0.8)



Energy savings for high latent load condition (SHF=0.6)



4. Study on hybrid GCHP systems for areas with unbalanced cooling and heating loads

4.1. Research in GCHP system for cooling load dominated buildings

- Hybrid GCHP (HGCHP) system with desuperheater
- HGCHP system with cooling tower
- HGCHP system with nocturnal cooling radiator

Research in GCHP system for cooling load dominated buildings

(1) HGCHP system with desuperheater




T Temperature sensor
 W Power monitor
 F Flow meter
 V Electrically-operated valve


Cooling or heating only mode: V3 and V4 on; V1, V2, V5 and V6 off;
 Cooling with DHW heating mode: V1, V2, V3 and V4 on; V5 and V6 off
 Heating with DHW heating mode: V1, V2, V3 and V4 on; V5 and V6 off
 DHW heating mode: V2, V5 and V6 on; V1, V3 and V4 off

■ Operating mode: Cooling/Heating/ DHW heating


Simulation Results of HGCHP system (1)




Comparisons of *COP* in different modes



Cooling with DHW mode




Heating with DHW mode



DHW heating mode

(2) HGCHP system with cooling tower







■ Cooling tower works as supplemental heat rejecter to reject the unbalanced cooling load, to prevent the heat accumulation around GHE and to ensure the system energy efficiency

Comparisons of energy consumptions between HGCHP system (2) and GCHP system (for office building with unbalance ratio of 1.59)

Item	HGCHP system				GCHP system
	Control strategy 1	Control strategy 2	Control strategy 3	Control strategy 4	
Annual operating time of CT (h)	290	555	1194	830	none
Highest temperature of water entering the heat pump (°C)	31.77	31.6	27.23	31.49	31.3
Annual energy consumption (kWh)	106794	101385	93577	111465	113034
Annual operating cost (\$)	6675	6337	5849	6967	7065
Borehole number of GHE		30			50
Initial cost of GHE (\$)		30000			50000
Initial cost of CT (\$)		312.5			none
Initial cost of heat pump and circulation pump (\$)		25625			
System initial cost (\$)		55938			75625
Sum of Initial cost and ten years operating cost (\$)	122684	119303	114423	125603	160247





- The optimal control strategy is the temperature difference control strategy.
- The optimal HGCHP system can reduce **35%** initial cost and **20.79%** operating cost in the first year operating, and can save **44.69%** operating cost and **40.05%** total cost in ten years operating compared with the common GCHP system



Comparisons of energy consumptions between HGCHP system (2) and GCHP system (for heavy cooling-dominated residential building)

Items	HGCHP system	GCHP system
Borehole length of the GHE (m)	240	400
Initial costs of the GHE (U.S. dollar)	9600	16 000
Initial costs of the CT (U.S. dollar)	50	NA
Initial costs of the heat pump and circulation pumps (U.S. dollar)	2500	2500
Initial costs of the whole system (U.S. dollar)	12 150	18 500
Annual energy consumption (kW)	14 300.57	18 536.93
Annual operating costs (U.S. dollar)	1735.06	2249.05
Ten years' energy consumption (kW)	143 076.41	308 272.62
Ten years' operating costs (U.S. dollar)	17 359.21	37 402.17
Sum of the initial and ten years' operating costs (U.S. dollar)	29 509.21	55 902.17

- The optimal control strategy is to activate the CT when the wet bulb temperature of ambient air is low.
- HGCHP system can save **34.32%** initial costs and **22.85%** operation costs in the first year running, and can save **53.59%** operating costs and **47.21%** total costs during ten years' operation compared with the GCHP system.





Conclusions

- Solar photovoltaic application develops very fast. The cost is nearly close to traditional energy resources for power generation.
- BIPV represents the future of renewable power generation in urban areas.
- Introduction of the FiT leads to bright future for BIPV in Hong Kong, but long-time policy is needed.
- Solar desiccant dehumidification is an effective way to produce cooling for air-conditioning.
- Research in hybrid GCHP systems can enhance the adaptability of GCHP technology, and can prompt the application of GCHP system in areas with unbalanced cooling and heating loads.



**Thank you for your
attention !**

Q & A